



## Product Overview

- Thread : PG, M (Metric) and NPT Thread
- Materials : UL Approved Nylon PA66, Flammability UL94V-2 for A, C, E Parts.
- Accept to make Flammability) UL94V-0 EPDM rubber for B, D Parts,
- Also accept to make super rubber : resist high temperature rubber, resist strong acid/alkali, etc.
- Protection Degree : IP68
- Working Temperature : -40°C to 100°C
- Features : The claws and seals of excellent design, sealing nut have a "Click" sound and re-open, can hold cable firmly a wider cable range.
- Resistant to salt water, weak acid, alcohol, oil, grease and common solvency
- Colours : Black (RAL9005), Gray (RAL7035) other color available upon request.



### PG TYPE

Product Model	Cable Range	Thread (O.D.) (C1)	Thread Length (C2)	Spanner Size	Qty / Bag
TPE-PG7-S	3-6.5	12.5	8.0	16.0	100
TPE-PG9-S	4-8	15.2	8.0	19.0	100
TPE-PG11-S	5-10	18.6	8.0	22.0	100
TPE-PG13.5-S	6-11	20.4	9.0	24.0	100
TPE-PG16-S	10-13	22.5	10.0	27.0	50
TPE-PG21-S	13-18	28.3	10.0	33.0	50

### M TYPE

Product Model	Cable Range	Thread (O.D.) (C1)	Thread Length (C2)	Spanner Size	Qty / Bag
TPE-M12x1.5-S	3-6.5	12.0	8.0	16.0	100
TPE-M16x1.5-S	4-8	16.0	9.0	19.0	100
TPE-M18x1.5-S	5-10	20.0	10.0	22.0	100
TPE-M20x1.5-S	6-12	22.0	10.0	24.0	100
TPE-M22x1.5-S	10-14	24.0	12.0	27.0	100
TPE-M25x1.5-S	13-18	25.0	15.0	33.0	50
TPE-M27x1.5-S	13-18	27.0	15.0	33.0	50