

## I Product Overview



Notes : Customization is available.

|                          |   |
|--------------------------|---|
| <b>Thread</b>            | Metric (M), PG, NPT   |
| <b>Material</b>          | Stainless Steel 304/316<br>Claw : PA<br>Sealing : NBR   |
| <b>Approvals</b>         | CE, RoHS, REACH   |
| <b>Protection Degree</b> | IP68  |
| <b>Temperature</b>       | -40°C to 100°C, Short time to 120°C   |
| <b>Features</b>          | Extremely easy installation, simply insert cable through the assembled gland and tighten gland, lock nut until cable is secured.<br><br>This cable glands are designed to withstand water, dust, salt, acid-base, alcohol, oil, and common solvent.<br><br>Cable can be lock, other end can access devices on box body<br>Also can choose thread according to the import and export for internal thread electric devices. |

| Thread Type | Product Model | Cable Range | Thread (O.D.) (C1) | Thread Length (C2) | Spanner Size | Qty / Bag |
|-------------|---------------|-------------|--------------------|--------------------|--------------|-----------|
| PG          | TPE-PG7-SS    | 3-6.5       | 12.5               | 6.0                | 14.0         | 100       |
|             | TPE-PG9-SS    | 4-8         | 15.2               | 7.0                | 17.0         | 100       |
|             | TPE-PG11-SS   | 5-10        | 18.6               | 7.0                | 20.0         | 100       |
|             | TPE-PG13.5-SS | 6-12        | 20.4               | 8.0                | 22.0         | 100       |
|             | TPE-PG16-SS   | 10-14       | 22.5               | 8.0                | 24.0         | 100       |
|             | TPE-PG21-SS   | 13-18       | 28.3               | 9.0                | 30.0         | 50        |
|             | TPE-PG29-SS   | 18-25       | 37.0               | 9.0                | 40.0         | 20        |
|             | TPE-PG36-SS   | 25-33       | 47.0               | 10.0               | 50.0         | 10        |
|             | TPE-PG42-SS   | 32-38       | 54.0               | 10.0               | 57.0         | 10        |
|             | TPE-PG48-SS   | 37-44       | 59.3               | 11.0               | 64.0         | 5         |
| TPE-PG63-SS | 42-52         | 70.8        | 15.0               | 78.0               | 5            |           |

| Thread Type | Product Model   | Cable Range | Thread (O.D.) (C1) | Thread Length (C2) | Spanner Size | Qty / Bag |
|-------------|-----------------|-------------|--------------------|--------------------|--------------|-----------|
| M           | TPE-M8x1.0-SS   | 2-5         | 8.0                | 5.0                | 12.0         | 100       |
|             | TPE-M10x1.0-SS  | 3-6.5       | 10.0               | 6.5                | 14.0         | 100       |
|             | TPE-M12x1.5-SS  | 4-8         | 12.0               | 8.0                | 14.0         | 100       |
|             | TPE-M16x1.5-SS  | 5-10        | 16.0               | 8.0                | 17.0         | 100       |
|             | TPE-M20x1.5-SS  | 6-12        | 20.0               | 8.0                | 22.0         | 100       |
|             | TPE-M25x1.5-SS  | 13-18       | 25.0               | 9.0                | 30.0         | 50        |
|             | TPE-M32x1.5-SS  | 15-22       | 32.0               | 10.0               | 40.0         | 20        |
|             | TPE-M40x1.5-SS  | 22-30       | 40.0               | 11.0               | 50.0         | 20        |
|             | TPE-M50x1.5-SS  | 32-38       | 50.0               | 13.0               | 57.0         | 10        |
|             | TPE-M63x1.5-SS  | 37-44       | 63.0               | 14.0               | 64.0         | 5         |
|             | TPE-M72x2.0-SS  | 42-52       | 72.0               | 16.0               | 78.0         | 5         |
|             | TPE-M75x2.0-SS  | 42-52       | 75.0               | 16.0               | 80.0         | 5         |
|             | TPE-M80x2.0-SS  | 55-60       | 80.0               | 18.0               | 88.0         | 5         |
|             | TPE-M88x2.0-SS  | 65-70       | 88.0               | 18.0               | 94.0         | 5         |
|             | TPE-M100x2.0-SS | 75-84       | 100.0              | 20.0               | 110.0        | 5         |

| Thread Type  | Product Model    | Cable Range | Thread (O.D.) (C1) | Thread Length (C2) | Spanner Size | Qty / Bag |
|--------------|------------------|-------------|--------------------|--------------------|--------------|-----------|
| NPT          | TPE-NPT3/8"-SS   | 4-8         | 17.0               | 8.0                | 18.0         | 100       |
|              | TPE-NPT1/2"-SS   | 6-12        | 21.2               | 8.0                | 22.0         | 100       |
|              | TPE-NPT3/4"-SS   | 13-18       | 26.5               | 9.0                | 30.0         | 50        |
|              | TPE-NPT1"-SS     | 18-25       | 33.2               | 11.0               | 40.0         | 20        |
|              | TPE-NPT1-1/4"-SS | 25-33       | 41.9               | 13.0               | 50.0         | 10        |
|              | TPE-NPT1-1/2"-SS | 32-38       | 48.0               | 14.0               | 57.0         | 10        |
|              | TPE-NPT2"-SS     | 37-44       | 60.0               | 14.0               | 65.0         | 5         |
|              | TPE-NPT2-1/2"-SS | 42-52       | 72.6               | 15.0               | 77.0         | 5         |
| TPE-NPT3"-SS | 65-70            | 87.8        | 15.0               | 94.0               | 5            |           |

\*\*บริษัทฯ ขอสงวนสิทธิ์การเปลี่ยนแปลงราคา โดยมีต้นฉบับแจ้งให้ทราบล่วงหน้า\*\*

ส่วนติดต่อการตลาด Tel 02-027-7841, 095-543-5665 / Fax 02-026-6529

Email : sales.tpetrading@gmail.com / ID Line : @tpetrading