

Product Overview



Thread	Metric (M), PG, NPT
Material	UL Approved Nylon PA66, Flammability UL94V-2 for A, C, E Parts. Accept to make Flammability) UL94V-0 EPDM rubber for B, D Parts, Also accept to make super rubber : resist high temperature rubber, resist strong acid/alkali, etc.
Temperature	-40°C to 100°C, Short Time 120°C
Protection Degree	IP68
Features	The claws and seals of excellent design, sealing nut have a "Click" sound and re-open, can hold cable firmly a wider cable range. Used to close to prevent dust or water against unused holes. and equipment having close threads.
Colours	Black (RAL9005) / White Gray (RAL7035)



Thread Type	Product Model	Cable Range	Thread (O.D.) (C1)	Thread Length (C2)	Spanner Size	Qty / Bag
PG	TPE-PG7-S	3-6.5	12.5	8.0	16.0	100
	TPE-PG9-S	4-8	15.2	8.0	19.0	100
	TPE-PG11-S	5-10	18.6	8.0	22.0	100
	TPE-PG13.5-S	6-11	20.4	9.0	24.0	100
	TPE-PG16-S	10-13	22.5	10.0	27.0	50
	TPE-PG21-S	13-18	28.3	10.0	33.0	50

Thread Type	Product Model	Cable Range	Thread (O.D.) (C1)	Thread Length (C2)	Spanner Size	Qty / Bag
M	TPE-M12x1.5-S	3-6.5	12.0	8.0	16.0	100
	TPE-M16x1.5-S	4-8	16.0	9.0	19.0	100
	TPE-M18x1.5-S	5-10	20.0	10.0	22.0	100
	TPE-M20x1.5-S	6-12	22.0	10.0	24.0	100
	TPE-M22x1.5-S	10-14	24.0	12.0	27.0	100
	TPE-M25x1.5-S	13-18	25.0	15.0	33.0	50
	TPE-M27x1.5-S	13-18	27.0	15.0	33.0	50